

## C5500 PT LM HITCH

## "Proven over time to be the best there is"

- Designed to mount to GMC C5500 model chassis.
- ► Pin on design permits off-season removal in minutes.
- Heavy duty angle, plate and tube construction for added strength.
- ► 3/4" thick upper attachment ears attach directly through chassis bumper to chassis frame rails.
- ► 3/8" thick lower cheekplates designed for stress transfer to chassis frame rails.





- Low mount power tilting design for tilt forward cabs when wing system is attached (not required if plow only).
- ► Wing tower tilts with hitch.
- 2-1/2" Diameter bore by 10" stroke double acting nitrided lift arm cylinder.
- Cylinder base angle is reinforced with 1/4" by 4" flat bar for added strength.
- Twin 4" x 3" x 1/4" HSS crosstubes for wing tower mounting. Hitch may also be used without crosstubes for plow mount only.
- Three attach pin heights on 23-1/2" centers using 1" diameter mounting pins.

Everest Equipment Co. 1077 Westmount Ayer's Cliff, QC, Canada J0B 1C0 Tel: (819)-838-4257 Fax: (819)-838-5653 www.everestequipment.com



Everest Equipment Co. reserves the right to change products and specifications without notice. AMERICAN SNO-PLOWS is a registered trading style of Everest Equipment Co.