

## "PT QC-DM" POWER TILT QUICK COUPLING HITCH

## "QUALITY by DESIGN"

- ► Intended for truck chassis with greater than 35,000 pound gross vehicle weight.
- ► Heavy duty angle, plate and tube construction for added strength.
- ► The bumper plate is adjustable for varying frame heights.
- ► 5/8" thick cheekplates designed for stress transfer to chassis frame rails.
- ► Hydraulically detachable front mast design permits off-season removal in minutes with upper and lower hydraulic mast locking pins.





- ► Power tilting for tilt forward cab design feature allowing the wing tower tilts with hitch.
- ➤ Twin 6" x 4" x 3/8" HSS crosstubes for wing tower mounting. Hitch may also be used without crosstubes for plow mount only.
- ▶ 4" Diameter bore by 10" stroke double acting nitrided lift ram cylinder providing over 16" of lift.
- Adjustable parking feet to allow for proper mast quick coupling and uncoupling.
- ►Three attach pin heights on 31" centers.
- ► Available adapter kit (not shown) for 21" centers.

Everest Equipment Co. 1077 Westmount Ayer's Cliff, QC, Canada J0B 1C0 Tel: (819)-838-4257 Fax: (819)-838-5653 www.everestequipment.com

