



**AMERICAN  
SNO-PLOWS**

# “GI” COMBO DUMP BODY SPREADER SERIES

“Proven over time to be the best there is”



Our “GI” series combination spreader / dump body gives you the capability to sand or salt roads during the winter season and use the unit as a conventional dump body to haul dirt and repair highways during the off season.

Our “GI” series changes quickly from dump mode to spreader mode with even weight distribution on both frame rails of the chassis.



**EVEREST EQUIPMENT CO.**

**HEAVY-DUTY SNOW & ICE CONTROL**





- ▶ Our GI spreaders are available in two lengths: 10.5' (GI-85) and 14' (GI-90T).
- ▶ These units feature smooth tapered dirt shedding sides with side posts constructed from 10 gauge Corten steel.
- ▶ Floor and tailgate are 3/16" Corten abrasion resistant steel.
- ▶ Two position hinged headboard allows for conventional box loading while in rear dump mode.
- ▶ The body hoists are NTEA class 50 (GI-85) and class 80 (GI-90T) rated and are twin arm underbody design.
- ▶ These spreaders provide 50° of rear tilt and 34° or 28° of front tilt in spreader mode for the GI-85 and GI-90T respectively.
- ▶ The switch to forward or rear tilt is safely performed at the curbside by relocating the non-load bearing, self-locking retainer shaft.

- ▶ Material is carried to the spinner by a chain conveyor located at the front of the body. The conveyor bed is recessed into the floor and is of 3/16" abrasion resistant steel.
- ▶ The spreader chain is 11" wide using #667X pintle type chain of 21,000 Lbs tensile strength.
- ▶ The material drops to a polymer chute mounted on the driver's side of the truck which leads to a hydraulically driven 18" poly spinner disk. The spinner assembly is removable for the off season.
- ▶ The GI's feature a take-up conveyor chain adjustment in two directions on both side of the conveyor.
- ▶ The conveyor is driven by a hydraulic motor via a 10:1 worm gear speed reducer.



Each of our GI combination spreader/dump bodies is equipped standard with underbody hoist, polymer spinner with hydraulic drive, polymer chute, conveyor chain cover and hose guide kit (Guide kit available only for the GI-90T).

### Optional Equipment

- ▶ Body vibrator kit.
- ▶ Removable screens, 3/8" diameter wire and 2-1/2" square openings.
- ▶ Frame mount cab shield protector.
- ▶ Air tailgate kit with cylinder and air lines.
- ▶ GI-85 and GI-90T double acting valve operating mechanism.
- ▶ Tailgate with three coal door chutes (available for GI-85 only).
- ▶ Polymer floor liner for both GI-85 and GI-90T.

Model	Length (inside)	Overall Length	Side Height	Tailgate Height	Capacity
GI-85	10'-6"	11'	26"	32"	7.3 Yards
GI-90T	14'	14'-6"	39" Front-31" Back (Tapered Sides)	40"	12.5 Yards

Everest Equipment Co.  
 1077 Westmount  
 Ayer's Cliff, QC,  
 Canada J0B 1C0  
 Tel: (819)-838-4257  
 Fax: (819)-838-5653  
[www.everestequipment.com](http://www.everestequipment.com)



**EVEREST EQUIPMENT CO.**  
**HEAVY-DUTY SNOW & ICE CONTROL**

