

"S1SA" STEEL REVERSIBLETRIP EDGE PLOW SERIES

"Proven over time to be the best there is"



- ► Oscillating drive bar on 31" centers.
- ▶3/8" Thick moldboard ribs.
- ▶39" or 45" moldboard heights.
- ► Hydraulic ram or worm gear sector reverse.
- ► Moldboard attaches to the drive frame at four points.
- ► Standard 1/2" by 8" C-1085 blade on 12" centers.

- ► Moldboard reverse 37 degrees either side of the bull dose position.
- ► Torsion spring trip edge design.
- ► 3-1/2" bore by 16" stroke reversing cylinders with cushion valve.
- ▶ 10 Gauge steel skin plate.



Model	Overall Length	Moldboard Height	Reverse Method	Cutting Edge Length	Moldboard Thickness
3910-S1SA-RR85	10'	39"		10'	10 Gauge Steel
3911-S1SA-RR85	11'	39"		11'	10 Gauge Steel
3912-S1SA-RR85	12'	39"		12'	10 Gauge Steel
3914-S1SA-RR85	14'	39"	Hydraulic or	14'	10 Gauge Steel
4510-S1SA-RR85	10'	45"	Worm Gear	10'	10 Gauge Steel
4511-S1SA-RR85	11'	45"		11'	10 Gauge Steel
4512-S1SA-RR85	12'	45"		12'	10 Gauge Steel
4514-S1SA-RR85	14'	45"		14'	10 Gauge Steel

Everest Equipment Co. 1077 Westmount Ayer's Cliff, QC, Canada J0B 1C0 Tel: (819)-838-4257

Tel: (819)-838-4257 Fax: (819)-838-5653 www.everestequipment.com



